TECHNICAL INFORMATION FOR







SHIELD PROTECTIVE CARPET FILM

Highly effective self-adhesive product, giving protection from foot traffic, debris, spills etc. during decoration and building works.

Note: Please ensure you have read and fully understood the usage guidelines before installation.



FEATURES



- Protects against dirt, stains, mess & spillages
- Will not move after application
- Waterproof
- · Easy to remove
- Suitable for most common carpet types
- Reverse wound for easy application
- Full batch traceability
- Date of production printed on inner core

PRODUCT RANGE

Product Code	Thickness (µm)	Width (mm)	Length (m)	Qty	Carton Qty
25CP	50	600	25	1	9
50CP	50	600	50	1	9
100CP	50	600	100	1	6

APPLICATION

- Ensure all surfaces are free from dust and contaminants, to aid with the adhesion process of application.
- Remove outer packaging from roll.
- Place roll in the direction it is to be applied, and unwind 12 inches (300mm) of film. Ensure that this section has adhered to the carpet surface either by hand or a brush/broom.
- Simply push the roll forward using hands or a brush/broom, ensuring that it rolls in a straight line.
- Smooth out with hands and feet as it unwinds.

PERFORMANCE DATA

Adhesive	Acrylic	
Environmental Condition Temperature	-5°C to 25°C	
Relative Humidity	90 ± 10%	
Shelf Life	12 months	

LIMITATIONS

- Shield Carpet Protector is not for use on hard surfaces.
- For improved adhesion to the carpet, vacuuming and removal of obstructions and dust is advised.
- Shield Carpet Protector must be removed within 30 days of application.
- In heavily trafficked areas, remove Shield Carpet Protector after a maximum of 1 week.
- Always check that the film has stuck firmly prior to commencing work.
- To check for compatibility, a test area is always recommended prior to full application
- Mop up any spillages as product may become slippery when wet, and replace film where necessary.
- Do not use under floor heating whilst the product is in situ.
- If in doubt when determining whether Shield Carpet Protector is suitable for use, contact TIMco technical support for further advice.
- Designed for use on synthetic carpets only. Do not use with wool or oriental carpets.
- Not suitable for use on rugs, worn carpets or loose fitted carpet tiles.

HEALTH & SAFETY

• Consult Safety Data Sheet (SDS03) for full list of hazards.

FIRE RATING



- Fire tests according to BS EN ISO 11925-2:2002
 Reaction to fire for building products Part 2: Ignitability when subjected to direct impingement of flame.
- Classified to BS EN 13501-1:2002 Fire classification of Construction Products and Building Elements: Part 1.

Contact the TIMco Technical Department for further information.