



FEBGROUT FLOWABLE UNIVERSAL GROUT

DECLARATION OF PERFORMANCE No. 14656665

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	FBGRTFLO25
2	INTENDED USE/S	Anchoring of reinforcing steel bar. Repair method 4.2 Conforming to the Annex ZA Table ZA.1
3	MANUFACTURER:	Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Ind. Estate Leeds, LS9 0SW
4	AUTHORISED REPRESENTATIVE:	N/A
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN 1504-6:2007
	Notified body/ies:	0086

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Pull out (dry) Displacement ≤0.6mm at load of 75kN	≤0.6mm	EN1881	EN1504-6:2007
Pull out (wet) Displacement ≤0.6mm at load of 75kN	≤0.6mm	EN1881	
Chloride ion content	≤0.05%	EN1015-7	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
 Function: Technical Product Coordinator
 At Leeds on 17 December 2019

Name : Andrew Stockill
 Function: QA/QC Coordinator
 At Leeds on 17 December 2019




End of information as required by Regulation (EU) No 305/2011





Everbuild Building Products LTD, Leeds, UK

DoP No. 14656665

EN 1504-6:2007

Notified Body 0086

Anchoring of reinforcing steel bar. Repair method 4.2
Conforming to the Annex ZA Table ZA.1

Pull out (dry) Displacement ≤ 0.6 mm at load of 75kN	≤ 0.6 mm
Pull out (wet) Displacement ≤ 0.6 mm at load of 75kN	≤ 0.6 mm
Chloride ion content	$\leq 0.05\%$

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

FBGRTFLO25

14656665

12/2019, ver. 01

1088

Template for translation. Only for
internal use

Declaration of Performance
FBGRTFLO25
14656665
12/2019 , ver. 01
1088

4/4

Template for translation. Only for
internal use

BUILDING TRUST

